## **CURVECUTTER DELTA 1500**

This machine is specially designed for cutting out segments of highest accuracy from a blank (i.e. bends, flat oval bends and domes). The Curvecutter Delta 1500 is a suitable machine for a high production line together with the Spiro<sup>®</sup> Rollformer, Stitchwelder and Gorelocker.



## **Unique Features**

- » Select from a wide range of programs ranging from 100 to 1500 mm diameter
- » Simple input for circular or flat-oval bends, angle cuts and other customized items
- » Accurate cutting of segments with high repeatability due to high-tech servo motors
- » No burrs and no hardening of the edge as a result of cutting with 4 roller-shears
- » Efficiency: 1 elbow 200 mm with 4 segments is cutting in 1 path within 15 seconds

Technical Data	
Maximum Sheet Width	1500 mm (60")
Material Thickness	0.4 - 1.1 mm (0.016"- 0.043") galvanized steel 0.4 - 0.6 mm (0.016"- 0.024") stainless steel 0.5 - 1.1 mm (0.020"- 0.043") aluminium
Cutting Speed	2 - 10 m/min. (6 – 32 fpm)
Segment Angle	5 - 46° (in steps of 1/10 degree)
Elbow Diameter	100 - 1500 mm (in steps of 1 mm) (4" - 60")
Number of Cutters	1 - 4 (selectable on control panel)

